



1 - LOW-PROFILE MANLID MULTIDO

ND500 MANLID GASKET for MS5		ND300 MANLID GASKET for MS3	
1113750019	14 x 14 PTFE/EPDM	1113750020	14 x 14 PTFE/EPDM
1113750015	14 x 14 Braided PTFE	1113750012	14 x 14 Braided PTFE
1113750018	14 x 14 Sweet White Rubber	1113750026	14 x 14 Sweet White Rubber
1113750040	14 x 12 PTFE/EPDM	1113750042	14 x 12 PTFE/EPDM

MANLID SWINGBOLT ASSEMBLY		MANLID WING NUT & SEALING	
1293869200	58mm Swingbolt ass. brass nut	1294260006	Wing nut brass
1293869100	83mm Swingbolt ass. brass nut	1118481011	Wing nut 316 St st
		1290951000	TIR sealing pin 304

2 - AIR INLET ATCO 1,5" BALL VALVE (AD3X or its previous version AD4X)

BALL SEALS		CAP & ACCESSORIES	
1114010001	Upper Ball Seal (PTFE) for AD3X	1114013000	Cap kit (including seal and chain)
1114010004	Lower Ball Seal (PTFE) for AD3X	1285970010	Cap seal (PTFE)
1296060010	Upper Ball Seal (PTFE) for AD4X	7021010002	Thermometer -40° +160°
1296060015	Lower Ball Seal (PTFE) for AD4X	7018060095	Pressure Gauge 0-6b St st

3 - TOP DISCHARGE

3" TANKFLY BUTTERFLY VALVE	
1285570001	Closure plate seal PTFE

FLAT GASKETS in CNAF/PTFE	
1190290000	ND50, round, int dia 50mm, ext dia 165mm, 4x18xPCD125 with cut side
1291400000	ND80, round, int dia 94mm, ext dia 185mm, 4x18xPCD160
1190920000	ND80, round, int dia 94mm, ext dia 200mm, 6x14xPCD168
1291480000	ND80, round, int dia 81mm, ext dia 200mm, 6x14xPCD168

4 - SAFETY RELIEF VALVE



2,5" BSP MEGASUPERVENTIX MX65F		3" FLANGED MEGASUPERVENTIX MX80	
1110015091	Flame proof gauze kit	1110019400	Flame proof gauze kit
1110019700	Spring set 4,4b	1110179400	Spring set 4,4b
1110019800	Spring set vacuum 0,21b	1110019800	Spring set vacuum 0,21b
7010150054	Pressure O'ring FEP/Si	7010150081	Pressure O'ring FEP/Si
7010150006	Vacuum O'ring FEP/Si	7010150006	Vacuum O'ring FEP/Si
1291310000	Setting Gasket CNAF/PTFE	1292040000	Setting Gasket Flat CNAF/PTFE 4 x 18 x PCD145 Ø176mm Ø82mm
1110016000	Flat Gasket, CNAF/PTFE, 6 x 11 x PCD105 Ø127mm Ø76mm	DRS80P484T20	Bursting disc, bursting pressure: 4.84 bar, at 20°C +/- 5%
DRS65P484T20	Bursting disc, bursting pressure: 4.84 bar, at 20°C +/- 5%		

5 - BOTTOM DISCHARGE: 3" TWINCO, TWINFLOW, NEATCO, NEATCO

FOOTVALVE		3" OUTLET NOZZLE & CAP	
7010150053	Footvalve ND80 O'ring Fep/Silicone	1285590001	3" PTFE seal for cap
		1285599100	3" Cap kit including seal and chain
		1285696000	3" BSP Outlet spigot flange
		1285690000	3" Outlet nozzle with cap & chain

FLAT GASKETS in CNAF/PTFE	
1291200000	Round Gasket, flat, CNAF/PTFE, int dia 109mm, ext dia 200mm, 8x14xPCD178, fit between footvalve and tank
1291390000	Square Gasket, flat, CNAF/PTFE, int dia 81mm, ext dia 144mm, 4 x Ø18 x PCD 160, fit between footvalve and butterfly valve
1291420000	Square Gasket, flat, CNAF/PTFE, int dia 90mm, ext dia 144mm, 4 x slotted hole Ø18 x PCD 145/162, fit between butterfly valve and outlet nozzle